




OVALEYE BOLT

Ovaleye Bolt



Minimum Tensile Strength 13,550 lbs

Catalog Number	Bolt Size Inch	Thread Length	Weight K.g.
MP-5806	5/8 x 6	4	.46
MP-5808	5/8 x 8	4	.47
MP-5809	5/8 x 9	4	.48
MP-3410	5/8 x 10	6	.55
MP-58012	5/8 x 12	6	.65
MP-5814	5/8 x 14	6	.68


Eyebolt are commonly used as an attachment point secure thimbles, clevises, Links and deadend insulators.

Feature

- Forged, one piece design\
- Supplied assemble with square nut
- Eye 1 1/2 x 2"

Double Hot dip galvanized

Ovaleye Double Arming



Minimum Tensile Strength 13,550 lbs

Catalog Number	Bolt Size Inch	Thread Per Inch	Weight 100 K.g.
MPF9612	5/8 x 12	10	
MPF9614	5/8 x 14	12	
MPF9616	5/8 x 16	14	
MPF9618	5/8 x 18	16	
MPF9620	5/8 x 20	18	
MPF9622	5/8 x 22	20	
MPF9624	5/8 x 24	22	
MPF9626	5/8 x 26	24	

- Double Arming Eyebolts are forged in one piece design and are commonly used as a combination double arming bolt as well as an eyebolt.
- Double arming the eyebolt are fully threaded the entire bolt length except for 2 inches under the eye. They are supplied assembled with three square nuts.

Double Hot dip galvanized